



Table 'D' Flanges

Dimensions in accordance with BS10:62.
Max hydraulic test pressure of 150lbf/in²

Imperial Measurements (inches)

NB	OD	Thickness	PCD	No of Bolts	Bolt Size
1/2	3 3/4	3/16	2 5/8	4	1/2
3/4	4	3/16	2 7/8	4	1/2
1	4 1/2	3 1/16	3 1/4	4	1/2
1 1/4	4 3/4	1/4	3 7/16	4	1/2
1 1/2	5 1/4	1/4	3 7/8	4	1/2
2	6	5/16	4 1/2	4	5/8
2 1/2	6 1/2	5/16	5	4	5/8
3	7 1/4	3/8	5 3/4	4	5/8
3 1/2	8	3/8	6 1/2	4	5/8
4	8 1/2	3/8	7	4	5/8
5	10	1/2	8 1/4	8	5/8
6	11	1/2	9 1/4	8	5/8
8	13 1/4	1/2	11 1/2	8	5/8

metric measurements (mm)

NB	OD	Thickness	PCD	No of Bolts	Bolt Size
15	95	5	67	4	M12x40
20	102	5	73	4	M12x40
25	114	5	83	4	M12x40
32	121	6	87	4	M12x40
40	133	6	98	4	M12x40
50	152	8	114	4	M16x50
65	165	8	127	4	M16x50
80	184	10	146	4	M16x50
90	203	10	165	4	M16x50
100	126	10	178	4	M16x55
125	254	13	210	8	M16x55
150	279	13	235	8	M16x55
200	337	13	292	8	M16x55