



Table 'E' Flanges

Dimensions in accordance with BS10:62.
Max hydraulic test pressure of 300lb/in²

Imperial Measurements (inches)

NB	OD	Thickness	PCD	No of Bolts	Bolt Size
1/2	3 3/4	1/4	2 5/8	4	1/2
3/4	4	1/4	2 7/8	4	1/2
1	4 1/2	9/32	3 1/4	4	1/2
1 1/4	4 3/4	5/16	3 7/16	4	1/2
1 1/2	5 1/4	11/32	3 7/8	4	1/2
2	6	3/8	4 1/2	4	5/8
2 1/2	6 1/2	13/32	5	4	5/8
3	7 1/4	7/16	5 3/4	4	5/8
3 1/2	8	15/32	6 1/2	4	5/8
4	8 1/2	1/2	7	4	5/8
5	10	9/16	8 1/4	8	5/8
6	11	11/16	9 1/4	8	3/4
8	13 1/4	3/4	11 1/2	8	3/4

metric measurements (mm)

NB	OD	Thickness	PCD	No of Bolts	Bolt Size
15	95	6	67	4	M12x40
20	102	6	73	4	M12x40
25	114	7	83	4	M12x40
32	121	8	87	4	M12x40
40	133	9	98	4	M12x40
50	152	9	114	4	M16x50
65	165	10	127	4	M16x50
80	184	11	146	4	M16x50
90	203	12	165	4	M16x55
100	126	13	178	8	M16x55
125	254	14	210	8	M16x55
150	279	17	235	8	M20x65
200	337	19	292	8	M20x65